



Model / Shape	Aqua-Sigma DIB-C750	Aqua-Sigma DIB-C750R	USPA UB-7000	USPA UB-7235	USPA UB-7035
Aqua-Sigma DIB Series	⊗	⊗			
USPA U Round			⊗	⊗	⊗
USPA L Elongated			⊗	⊗	⊗

PLEASE NOTE: The electronic bidet seat is designed to be installed on a toilet bowl in place of a conventional seat. Our bidet seats will not fit precisely to all toilets please measure your toilet as indicated in the confirmation chart below to confirm which seat shape will be most suited to your toilet. The surface of the toilet should be flat without reliefs or raised ridges.

The seat requires a mains water supply of between 0.07 Mpa (0.7 bar) and 0.74 Mpa (7.4 bar) pressure. A fully compliant power source (in U.K. to BS7671) within 1.5 m of centre line of the toilet (230V 50Hz 1.7Kw max 10A fuse rating)

Seat Shape and Size

Aqua-Sigma DIB Series	USPA U Round	USPA L Elongated

Toilet Bowl Measurements to Confirm

	Aqua-Sigma DIB Series	USPA U Round	USPA L Elongated
A	430 ~ 450mm	430 ~ 470mm	455 ~ 490mm
B	Over 40mm	Over 40mm	Over 40mm
C	120 ~ 210mm	140 ~ 240mm	140 ~ 220mm
D	Minimum 315mm	Minimum 315mm	Minimum 350mm
E	Minimum 500mm	Minimum 500mm	Minimum 520mm

