

OVERVIEW OF WASHLET FUNCTIONS

NEOREST AC



NEOREST EW



SG WASHLET



GIOVANNONI



GL WASHLET



EK WASHLET



	NEOREST AC	NEOREST EW	SG WASHLET	GIOVANNONI	GL WASHLET	EK WASHLET
CLEANSING FUNCTIONS	COMFORT SPRAY REAR	•	•	•	•	•
	COMFORT SPRAY REAR SOFT	•	•	•	•	•
	COMFORT SPRAY FRONT WASH	•	•	•	•	•
	OSCILLATING COMFORT SPRAY	•	•	•	•	•
	MASSAGE SPRAY	•	•	•	•	•
	ADJUSTABLE WATER PRESSURE	•	•	•	•	•
	ADJUSTABLE POSITION	•	•	•	•	•
HYGIENE FUNCTIONS	ACTILIGHT	•	•	•	•	•
	EWATER+	•	•	•	•	•
	REMOVABLE WASHLET UNIT	•	•	•	•	•
	SELF-CLEANING WAND JET	•	•	•	•	•
	SELF-CLEANING WAND JET WITH EWATER+	•	•	•	•	•
	DEODORISER – AIR-CLEANING FILTER SYSTEM	•	•	•	•	•
	COATED WAND JET *	•	•	•	•	•
	CEFIONTECT GLAZE	•	•	•	•	•
	RIMLESS DESIGN	•	•	•	•	•
	TORNADO FLUSH	•	•	•	•	•
COATED TOILET SEAT (TOP AND BOTTOM) *	•	•	•	•	•	
COMFORT FUNCTIONS	NIGHTLIGHT	•	•	•	•	•
	SENSOR-ACTIVATED LID	•	•	•	•	•
	SENSOR-ACTIVATED FLUSH	•	•	•	•	•
	SOFT-CLOSING SEAT	•	•	•	•	•
	REMOTE CONTROL	•	•	•	•	•
	DRYER WITH ADJUSTABLE TEMPERATURE	•	•	•	•	•
	HEATED SEAT WITH ADJUSTABLE TEMPERATURE	•	•	•	•	•
	MEMORY FUNCTION FOR TWO PEOPLE	•	•	•	•	•
	MAINTENANCE-FREE	•	•	•	•	•
	CONTINUOUS-FLOW WATER HEATER	•	•	•	•	•
ECO	ENERGY SAVER TIMER	•	•	•	•	•
	ENERGY SAVER AUTO	•	•	•	•	•
	NO CHEMICAL CLEANERS REQUIRED	•	•	•	•	•

* silicone-based alloy

OVERVIEW OF TECHNICAL DATA

	NEOREST AC	NEOREST EW		SG WASHLET	GIOVANNONI	GL WASHLET	EK WASHLET
WARM WATER SPRAY	COMFORT SPRAY FLOW RATE	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.29 to 0.55 l/min	0.29 to 0.55 l/min	0.29 to 0.6 l/min
	SOFT FLOW RATE	0.32 to 0.43 l/min	0.32 to 0.43 l/min	0.32 to 0.43 l/min			
	LADY SHOWER FLOW RATE	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0.27 to 0.55 l/min	0.27 to 0.55 l/min	0.27 to 0.55 l/min
	CONTINUOUS-FLOW WATER HEATER	•	•	•			
	WARM WATER TANK				0.7 l	0.7 l	0.78 l
	WARM WATER SUPPLY	unlimited	unlimited	unlimited	up to 2 minutes	up to 2 minutes	up to 2 minutes
	ADJUSTABLE WATER TEMPERATURE	30 to 40 °C	30 to 40 °C	30 to 40 °C	30 to 40 °C	30 to 40 °C	35 to 40 °C
	WATER TANK REHEATING TIME				approx. 10 min	approx. 10 min	approx. 10 min
COMFORT	HEATED SEAT, INDIVIDUALLY ADJUSTABLE TEMPERATURE	28 to 35 °C	28 to 35 °C	28 to 36 °C	28 to 35 °C	28 to 35 °C	28 to 35 °C
	DEODORISER – FILTER SYSTEM PERFORMANCE	normal 0.09m ³ /min, power 0.16m ³ /min	normal 0.09m ³ /min, power 0.16m ³ /min	normal 0.09m ³ /min, power 0.16m ³ /min	normal 0.09 m ³ /min, power 0.16m ³ /min	normal 0.09m ³ /min, power 0.16m ³ /min	
	DRYER WITH ADJUSTABLE TEMPERATURE	35 to 55 °C	35 to 55 °C	35 to 55 °C			
CONNECTIONS/PIPES	POWER OUTLET REQUIRED	•	•	•	•	•	•
	WATER CONNECTION PRESSURE	1 to 10 bar	1 to 10 bar	1 to 10 bar	1 to 10 bar	1 to 10 bar	1 to 10 bar
	POWER INPUT	1289–1527 W	1289–1527 W	1289–1527 W	270–320 W	270–320 W	269–315 W
	CONNECTION LIMITS	220–240 V/50 HZ	220–240 V/50 HZ	220–240 V/50 HZ	222–240 V/50 HZ	221–240 V/50 HZ	221–240 V/50 HZ
ECO	STAND-BY	choose 3, 6 and 9 hours	choose 3, 6 and 9 hours	choose 3, 6 and 9 hours	choose 3, 6 and 9 hours	choose 3, 6 and 9 hours	choose 6 and 9 hours
	EN 1717 (DRINKING WATER SAFETY)	•	•	•	•	•	•

CERAMIC/WASHLET COMBINATIONS

	CERAMIC					
	NEOREST (with zirconium coating)	NEOREST (with CeFIONtect glaze)	SG	GIOVANNONI	MH	NC
WASHLET	•					
NEOREST AC	•					
NEOREST EW		•				
SG			•			
GIOVANNONI				•		
GL					•	•
EK					•	•