

## Product description

## Rapid SL for GROHE Sensia® IGS shower WC

flushing cistern GD 2 with connections for GROHE Sensia shower toilets (GROHE Sensia IGS/GROHE Sensia Arena) with maintenance access

## 1.13 m finished installation height

for on-the-wall installations or studded walls powder coated steel frame, self-supporting for dry-cladding, completely pre-assembled with fixed connections

for single or series installation quick adjustment, lockable fixing material

TÜV approved 2 WC fixing bolts fixing device for ceramic

distance of fixing bolts 180/230 mm PP outlet bend Ø 90 mm depth adjustable

reducer Ø 90/110 mm

inlet and outlet connecting set flushing cistern GD 2, 6 - 3 I pneumatic discharge valve offering 2 modes of

operation: dual flush or single flush rear water supply

low noise (group I acc. to

German Noise Specification) Insulated against condensation

1/2" water supply connection including integrated

angle valve and push fit flexible hose union no tools required for the installation of the inspection shaft incl. protection

during construction phase for vertical or horizontal use

2 wall brackets with fixing material

universal water connection for shower toilets Sensia Arena and Sensia IGS

concealed socket for mains supply positioning help for electrical connection

for mounting of small flush plates please order revision shaft 40 911 000 (sold separately)

Flow pressure diagram

Dimensional drawings no colour (001) Spare parts/ Exploded drawing no colour (001)



